




CERTIFIED
LUXEON
LUMINAIRE MANUFACTURER

Features

- 22 high intensity red, green, blue, amber or white K2 Luxeon emitters
- Custom LED arrays available by request
- Highest quality color binning
- LED beam angle 8° full angle (other angles available upon request)
- Extensive color palette
- Light shaping diffusion lenses available to vary output beam angle

Preset Programming

- Pre-programmed with 2 overlapping sets of effects, each with 31 patterns
- High frequency strobing up to 28 frames per second (variable up to 10min)
- Programmable offset for synchronizing effects over multiple fixtures
- Provides an alternative projection medium for video manipulation software

Control

- Selectable dimming curve option including a new smooth dimmer curve that emulates dimming of a tungsten lamp
- 4 digit alpha-numeric display indicates fixture address and menu functions
- Features real time readout display
- DMX 512 input and output 5pin XLR standard
- Master/slave capabilities
- Default factory reset (simple 2 button reset)
- RDM ready
- Selectable DMX address

Cooling

- Proprietary patent pending heat management system, based around a substantial heat sink construction
- Internal quiet fan cooling system

Construction

- Robust housing suitable for both permanent and temporary applications

Finish

- Powder coated black (other colors available to order at an additional cost)

Weight

- With yoke 4.8lbs (2.2kg)
- Without yoke 4.2lbs (1.9kgs)

Dimensions

- 8.1" (206mm) length x 6.5" (166mm) width x 3.4" (84mm) height

Electrical

- Auto ranging 100-250 vac power supply 50-60 hz
- Power via a Powercon 20A connectors, power can be daisy chained
- Data via 5pin XLR chassis mounted connectors, data can be daisy chained

Power Consumption

- Low power consumption (66 watts at full intensity) virtually no heat generated

IP20 (dry) fixture

UL LISTED

ACCESSORIES

- 10° Light Shaping Diffusion kit
- 20° Light Shaping Diffusion kit
- 30° Light Shaping Diffusion kit
- 40° Light Shaping Diffusion kit
- 60°x1 linear Light Shaping Diffusion kit
- 1x60° linear Light Shaping Diffusion kit

